

RMLL Series LED Luminaries



Craftech LED Machine Lights are compact, robust and efficient. It provides bright and uniform light distribution improving productivity and safety in operations. It is suitable for light as well as heavy industrial applications. It is constructed with heavy duty extruded aluminum and tempered glass with frosted surface finish to minimize glare on eyes. With estimated working life of more than 50,000 hours.

Product Specifications

Light diffuser	5mm Clear / Frosted Glass
Housing material	Anodized Aluminium Housing 6063 Grade
Mounting arrangement	"L" Clamp, rotatable mounting
LED Type	LM 80 Approved, 0.5W/1W LED
LED Light Angle, Color, CRI	120 Deg, 6500K, >80
Luminaire Light Yield	110-120 Lumens / Watt
Insulation resistance at 500 VDC	1.3 X 10 ⁴ Mega - Ohm
Operating temperature	-20°C to +65°C
Operating Life	>50,000 Hours
Ingress Protection	IP 67
Standard Conformity, Degree of Protection	IEC 60947, IEC 60529, IEC 60068 , IP67

RMLL Series LED Luminaries

Product Drawing



Product Specification and Dimension

Sr.no	P/N	Input voltage/Wattage	Size L1(mm)	Size L2(mm)	Size L3(mm)
1	CR-RMLL-24-D-12W	24VDC, 12W	240	300	320
2	CR-RMLL-24-D-18W	24VDC, 18W	360	420	440
3	CR-RMLL-24-D-24W	24VDC, 24W	475	535	555
4	CR-RMLL-24-D-30W	24VDC, 30W	600	660	680
5	CR-RMLL-24-D-36W	24VDC, 36W	600	660	680

